

Inventory for Lot-96394: EMPG Downhole Completion & Wellhead Equipment										
MATERIAL	DESCRIPTION	SELLER DESCRIPTION	Manufacturer	Model / Type	Connection / Size	Alloy / Material	Working Pressure	Unit Tag / Serial No.	Qty	Notes / Flags
204257	Landing Nipple / Ball Valve, RQ profile	LANDNIP_RQ_4 1/2_FOX_ZXZ_INC925	Halliburton	911MRQ36801	4-1/2" FOX ZXZ	Incoloy 925	N/A	UT-792	1	OD 127.5mm (5.02"), length ~48.5", 1/8" NPT control line port
204257	Landing Nipple / Ball Valve, RQ profile	LANDNIP_RQ_4 1/2_FOX_ZXZ_INC926	Halliburton	911MRQ36801	4-1/2" FOX ZXZ	Incoloy 925	N/A	UT-625	1	
204257	Landing Nipple / Ball Valve, RQ profile	LANDNIP_RQ_4 1/2_FOX_ZXZ_INC927	Halliburton	911MRQ36801	4-1/2" FOX ZXZ	Incoloy 925	N/A	UT-752	1	
204257	Landing Nipple / Ball Valve, RQ profile	LANDNIP_RQ_4 1/2_FOX_ZXZ_INC928	Halliburton	911MRQ36801	4-1/2" FOX ZXZ	Incoloy 925	N/A	UT-785	1	
204257	Landing Nipple / Ball Valve, RQ profile	LANDNIP_RQ_4 1/2_FOX_ZXZ_INC929	Halliburton	911MRQ36801	4-1/2" FOX ZXZ	Incoloy 925	N/A	Not individually tagged	1	
409403	Landing Nipple / Ball Valve, RRQ profile	LANDNIP_RRQ_4 1/2_FOX_ZXZ_INC.925	Halliburton	911RRQ38134	4-1/2" FOX ZXZ (3.813" bore)	Alloy 925	N/A	UT-444 / UT-445	1	Heat HH9177XV11, 6.25" dia. rod stock cert (Special Metals / Howco)
427037	Tubing-Retrivable SCSSV, TRMAXX-10E	TBG_SVLNE_TRMAXX_4 1/2_FOX_MXZ_CR13	Schlumberger / Cameron	100524277	3.813" RQ x 7.923" OD	Super 13Cr	10,000 PSI	UT-801 (SN HABS-27)	1	Surface-controlled subsurface safety valve, temp rating +40F to +300F
427037	Tubing-Retrivable SCSSV, TRMAXX-10E	TBG_SVLNE_TRMAXX_4 1/2_FOX_MXZ_CR14	Schlumberger / Cameron	100524277	3.813" RQ x 7.923" OD	Super 13Cr	10,000 PSI	UT-802 (SN HABS-28)	1	
427037	Tubing-Retrivable SCSSV, TRMAXX-10E	TBG_SVLNE_TRMAXX_4 1/2_FOX_MXZ_CR15	Schlumberger / Cameron	100524277	3.813" RQ x 7.923" OD	Super 13Cr	10,000 PSI	UT-895 (SN CZS-0225)	1	
406606	Annular Safety Valve, ASV-YAO	USV_ANNULAR_ASV_YAO_3 1/2_FOX_ZXM_INC925	Halliburton	388444	3-1/2" FOX ZXM	Incoloy 925 body / MP35N spring	8,000 PSI (test 12,000)	UT-748 (SN 102794281)	1	OD 5.963", ID 2.97", length 49"
406606	Annular Safety Valve, ASV-YAO	USV_ANNULAR_ASV_YAO_3 1/2_FOX_ZXM_INC926	Halliburton	388444	3-1/2" FOX ZXM	Incoloy 925 body / MP35N spring	8,000 PSI (test 12,000)	UT-187 (SN 101288193-x)	1	
405093	Tubing Packer, Permanent Retainer	TBG-PACKER_PERMANENT_RETAINER_7" CR	Weatherford	N/A	7" casing	L80 / CR13-95	N/A	UT-862	1	Related but not in this inventory: chem. injection sub 405091, anchor seat assy 405092, ported sealbore ext. 405095
407696	Permanent Packer, UltraPak UL	TBG-PACKER_PMNT_RET_7" 32-35# INC.718	Weatherford	758098 / mandrel 758099	7" 32-35# x 4.75" x 4.00"	Inconel 718 body / 80hd HNBR element	N/A	UT-1396 (SN 79003570-1)	1	Anchor Seal 407690 and not included.
631085	Single String Solid Block (SSSB) Wellhead Assembly	SOLID-BLOCK_13 5/8X3 1/16_700_4 1/8_SRL	Cameron	Style FH / Model FLS, P/N 2263348-45-31	13-5/8" x 3-1/16"	CF-13 (13Cr) — API 6A Mat Class CC,FF-NL	10,000 PSI	SN 112386365001	1	Manually actuated double master + single swab valve; API 6A 20th Ed, Temp Class P+U, PS13, PR2. Surface wellhead component.